


MAGNETIC RESONANCE IMAGING DEVICE

Patent number: JP2001149338
Publication date: 2001-06-05
Inventor: TAKESHIMA HIROTAKA; YAO TAKESHI; HONNA TAKAO; TAKANO HIROSHI; YOSHINO HITOSHI; MOTOSHIROMIZU HIROBUMI; NEMOTO YASUHIRO; ISHII HIROSHI
Applicant: HITACHI MEDICAL CORP
Classification:
- international: **A61B5/055; G01R33/28; A61B5/055; G01R33/28;**
(IPC1-7): A61B5/055; G01R33/28
- european:
Application number: JP19990335263 19991126
Priority number(s): JP19990335263 19991126

Report a data error here

Abstract of JP2001149338

PROBLEM TO BE SOLVED: To provide an inclined magnetic field coil structure of low vibration and low noise and a fixing structure therefor in a magnetic resonance imaging device having magnetostatic field generating sources having a high opening characteristic.
SOLUTION: Two sets of magnetostatic field generating sources are oppositely arranged in the vertical direction, and two sets of almost flat coil assemblies 14 are oppositely arranged by sandwiching a uniform magnetic field area (a measuring space) formed between both magnetostatic field generating sources. The coil assemblies 14 are composed of a main coil 5 for generating an inclined magnetic field in the measuring space, a shield coil 6 for shielding this external magnetic field and an intermediate member 13 arranged between both coils. The intermediate member 13 is composed of a highly rigid material. Plural vibration damping materials 30 are arranged in an outer peripheral part of the intermediate member 13, and a bolt 25 of a fixing tool is implanted in a surface of a cooling vessel (a stationary object) 2 corresponding to these vibration damping materials. The intermediate member 13 of the coil assemblies 14 is fixed to the cooling vessel 2 by the bolt 25 via the vibration damping materials 30.



Data supplied from the **esp@cenet** database - Worldwide